

Rasco Industries, Inc.
 5310 Shoreline Drive
 Mound, MN 55364
 United States
Phone: 800-537-3802
 Fax: 952-283-1261
 Sales@Rascoind.com



RASCO
INDUSTRIES, INC.
 BUGBLOCKER.COM

P.O. NO: _____

DATE REQUIRED: _____

TAG: _____

SPECIAL INSTRUCTIONS: _____

QUANTITY: _____

PREPARED BY: _____

EMAIL: _____

COMPANY: _____

ADDRESS: _____

PHONE: _____

FAX: _____

SHIP TO ZIP: _____

Bug Blocker® Screen Door - Fixed in Opening

- A) Opening Width _____ ft _____ in
- B) Opening Height _____ ft _____ in
- C) Are the building and opening square? y n
- D) Which option for attachment?
 - Semi-Permanent
 - Removable or
- E) 12 Mesh
- 30 Mesh or
- Expanded Metal



Top View for Attachment Options



Semi Permanent - Aluminum
 2 x 2 angles attached to sides

Use self drilling screws to drill
 through 2 x 2 and into door
 section stiles.

Removable - Aluminum 1-1/2
 x 3-1/2 angles attached to
 sides

Drill 3/8 clearance holes
 through the 3-1/2" leg to
 match pem nuts in end stiles.

Sections will be made slightly smaller than opening so they can stack in the opening. There will be a weather astragal on the bottom section. There will be brush seal for the top.