

Rasco Industries, Inc.
 5310 Shoreline Drive
 Mound, MN 55364
 United States
 Phone: 800-537-3802
 Fax: 952-283-1261
 Sales@Rascoind.com



RASCO
 INDUSTRIES, INC.
 BUGBLOCKER.COM

P.O. NO: _____

DATE REQUIRED: _____

TAG: _____

SPECIAL INSTRUCTIONS: _____

QUANTITY: _____

PREPARED BY: _____

EMAIL: _____

COMPANY: _____


ADDRESS: _____

PHONE: _____

FAX: _____

SHIP TO ZIP: _____

Chain Link Security Door - Vertical Lift / Switch Track



- A) Any interference for Rasco track? y n
- B) Existing Door Thickness _____ in
- C) Existing Track Width _____ in
- D) Existing track in good condition? y n
- E) In the open position, can existing door stop a minimum of 7" above the opening? y n
- F) Opening Width _____ ft _____ in
- G) Opening Height _____ ft _____ in
- H) Existing Door Width _____ ft _____ in
- I) Existing Door Height _____ ft _____ in
- J) Existing Track Outside-to-Outside _____ ft _____ in
- K) Distance from Existing Track to Bollard _____ ft _____ in
- L) Is existing door motorized? y n
 Provide Interlock Switch on new track? y n
- M) Will Rasco door be motorized? y n
 Provide Interlock Switch and Solid Shaft? y n
- N) If yes, is Rasco providing the operator? y n
- O) If the graduated hinge count is not typical (1,2,3,4, etc...), what is it? _____

Notes: A torsion bar support is required on all doors 10' or wider and a solid shaft if 12' or wider. Switch track cannot be used if existing door has outside pull cables. or has TKO, Workhorse or Barcol type tracks.